

COMPRESSORI A CANALE LATERALE - DOPPIOSTADIO



tipo	mas. volume d'aria aspirata [m ³ /h] 50/60Hz	mas. Pressione [mbar abs.] 50/60Hz	mas. Pressione [mbar rel.] 50/60Hz	mas. potenza del motore [KW] 50/60Hz
SV 5.90/2	42/50	1240/1225	+240/+225	0,37/0,44
SV 130/2	70/80	1160/1140	+160/+140	0,55/0,66
SV 130/2	70/80	1250/1230	+250/+230	0,75/0,9
SV 130/2	70/80	1400/1390	+400/+390	1,1/1,29
SV 200/2	90/110	1300/1260	+300/+260	1,1/1,29
SV 200/2	90/110	1410/1430	+410/+430	1,5/1,8
SV 201/2	90/110	1260/1230	+260/+230	1,1/1,29
SV 201/2	90/110	1420/1400	+420/+400	1,5/1,8
SV 300/2	160/190	1330/1280	+330/+280	2,2/2,65
SV 300/2	160/190	1515/1450	+515/+450	3,0/3,6
SV 400/2	210/250	1330/1290	+330/+290	3,0/3,6
SV 400/2	210/250	1500/1450	+500/+450	4,0/4,8
SV 500/2	260/305	1370/1340	+370/+340	4,0/4,8
SV 500/2	260/305	1480/1530	+480/+530	5,5/6,6
SV 700/2	370/440	1330/1270	+330/+270	5,5/6,6
SV 700/2	370/440	1500/1470	+500/+470	7,5/9,0
SV 1100/2	520/610	1260/1180	+260/+180	7,5/9,0
SV 1100/2	520/610	1500/1410	+500/+410	11,0/13,2
SV 220/2 uw	110/132	1320/1260	+320/+260	1,6/1,8
SV 300/2 uw	150/180	1400/1330	+400/+330	2,8/3,3
SV 320/2 uw	160/190	1700/1570	+700/+570	4,9/5,8