

# COMPRESSORI A PALETTE, FUNZIONANTI A SECCO



tipo	mas. volume d'aria aspirata [m <sup>3</sup> /h] 50/60Hz	mas. Pressione [mbar abs.] 50/60Hz	mas. Pressione [mbar rel.] 50/60Hz	mas. potenza del motore [KW] 50/60Hz
<b>DT 4.2</b>	1,9/2,3	1600/1600	+600/+600	0,09/0,105
<b>DT 4.4</b>	4,2/4,9	2000/2000	+1000/+1000	0,18/0,21
<b>DT 4.6/0-61</b>	5,7/6,4	1500/1500	+500/+500	0,18/0,21
<b>DT 4.8</b>	8/9,5	2000/2000	+1000/+1000	0,35/0,42
<b>DT 4.10</b>	10/12	2000/2000	+1000/+1000	0,37/0,45
<b>DT 4.16</b>	16/19	2000/2000	+1000/+1000	0,55/0,75
<b>DT 4.25 K</b>	25/30	2000/2000	+1000/+1000	1,10/1,30
<b>DT 4.40 K</b>	40/48	2000/2000	+1000/+1000	1,85/2,20
<b>DX 4.10</b>	10/12	2000/2000	+1000/+1000	0,37/0,45
<b>DX 4.16</b>	16/19	2000/2000	+1000/+1000	0,55/0,75
<b>DX 4.25 K</b>	25/30	2000/2000	+1000/+1000	1,10/1,30
<b>DX 4.40 K</b>	40/48	2000/2000	+1000/+1000	1,85/2,20
<b>DT 4.25/0-80</b>	25/30	1600/1600	+600/+600	0,75/0,90
<b>DT 4.40/0-80</b>	40/48	1500/1500	+500/+500	1,25/1,50
<b>DX 4.25/0-80</b>	25/30	1600/1600	+600/+600	0,75/0,90
<b>DX 4.40/0-80</b>	40/48	1500/1500	+500/+500	1,25/1,50
<b>KDT 3.60</b>	54/63	2500/2500	+1500/+1500	3,00/3,50
<b>KDT 3.80</b>	66/77	2500/2500	+1500/+1500	4,00/4,80
<b>KDT 3.100</b>	99/118	2500/2500	+1500/+1500	5,50/6,40
<b>KDT 3.140</b>	129/153	2500/2500	+1500/+1500	7,80/9,30
<b>KDX 3.60</b>	54/63	2500/2500	+1500/+1500	3,00/3,50
<b>KDX 3.80</b>	66/77	2500/2500	+1500/+1500	4,00/4,80
<b>KDX 3.100</b>	99/118	2500/2500	+1500/+1500	5,50/6,40
<b>KDX 3.140</b>	129/153	2500/2500	+1500/+1500	7,80/9,30
<b>DTLF 2.200</b>	174/216	3000/3000	+2000/+2000	11,0/12,5
<b>DTLF 2.250</b>	247/294	3000/3000	+2000/+2000	15,0/18,0
<b>DTLF 2.360</b>	360/-	1900/-	+900/-	15,0/-
<b>DXLF 2.200</b>	174/216	3000/3000	+2000/+2000	11,0/12,5
<b>DXLF 2.250</b>	247/294	3000/3000	+2000/+2000	15,0/18,0
<b>DTLF 2.400</b>	365/440	2800/2800	+1800/+1800	18,5/22,0
<b>DTLF 2.500</b>	515/600	2800/2800	+1800/+1800	30,0/34,5
<b>DXLF 2.400</b>	365/440	2800/2800	+1800/+1800	18,5/22,0
<b>DXLF 2.500</b>	515/600	2800/2800	+1800/+1800	30,0/34,5
<b>VARIAIR</b>	mas. volume d'aria aspirata [m <sup>3</sup> /h]	mas. Pressione [mbar abs.]	mas. Pressione [mbar rel.]	mas. potenza del motore [KW]
<b>KDT 3.80/0-400</b>	79	2500	+1500	4,00
<b>KDT 3.100/0-400</b>	118	2500	+1500	7,50
<b>KDT 3.140/0-400</b>	150	2500	+1500	7,50
<b>DTLF 2.250/0-400</b>	285	2800	+1800	15,0
<b>DTLF 2.500/0-400</b>	584	2500	+1500	22,0