

**VARIAIR**

	mas. Volume d'aria aspirata [m <sup>3</sup> /h]	mas. vuoto [mbar abs.]	mas. vuoto [mbar rel.]	mas. potenza del motore [KW]
<b>KVT 3.100/0-400</b>	112	100	-900	4,00
<b>KVX 3.100/0-400</b>	112	100	-900	4,00
<b>KVT 3.140/0-400</b>	145	100	-900	4,00
<b>KVX 3.140/0-400</b>	145	100	-900	4,00
<b>VTLF 2.250/0-400</b>	280	200	-800	7,50
<b>VXLF 2.250/0-400</b>	280	200	-800	7,50
<b>VTLF 2.360/0-400</b>	405	250	-750	13,2
<b>VTLF 2.500/0-400</b>	560	250	-750	11,0
<b>VXLF 2.500/0-400</b>	560	250	-750	11,0

**VARIAIR**

	mas. Volume d'aria aspirata [m <sup>3</sup> /h]	mas. vuoto [mbar abs.]	mas. vuoto [mbar rel.]	mas. potenza del motore [KW]
<b>KDT 3.80/0-400</b>	79	2500	+1500	4,00
<b>KDT 3.100/0-400</b>	118	2500	+1500	7,50
<b>KDT 3.140/0-400</b>	150	2500	+1500	7,50
<b>DTLF 2.250/0-400</b>	285	2800	+1800	15,0
<b>DTLF 2.500/0-400</b>	584	2500	+1500	22,0